



## BentoPro Granules

### Product Description

BentoPro Granules are bentonite clay granules used as a detail material in conjunction with the EPRO waterproofing membranes.

### Basic Uses

BentoPro Granules are designed for waterproofing below grade structural slabs as well as construction methods incorporating lagging, concrete caisson or shotcrete retention walls.

### Packaging

50 lb. Bags

### APPLICATION

Use BentoPro Granules at the base of foundation walls, at vertical to horizontal transitions, to detail penetrations and to fill voids, and in the seams of BentoPro in horizontal applications.

For complete details, refer to EPRO's published architectural Guidelines or the EPRO website [www.eproserv.com](http://www.eproserv.com).

### INSTALLATION

Lay Granule bag on its side, cut a 1" opening in the lower corner. Dispense a 1 ½" to 2" (38 mm to 50 mm) bentonite cant along all vertical to horizontal transitions or on horizontal seams. One 50 lb Granule bag should cover approximately 45 to 50 linear feet.

### MAINTENANCE

BentoPro Granules requires no maintenance after installation.

### LIMITED WARRANTY

Epro Services, Inc. warrants its products will be delivered free of defects in materials and workmanship. EPRO will replace the material or refund the purchase price. EPRO makes no other warranty, including an implied warranty of merchantability or fitness for a particular purpose. EPRO shall not be liable for any other loss or damage. Contact EPRO to discuss specific details for extended warranty periods.

### TECHNICAL DATA

Screen Analysis:	Typical
Dry Screen, 16 mesh	100%
Dry Screen, 10 mesh	1.7%
Wet Screen 200 mesh	1.3%
AFS Grain Fineness	25
Industrial Properties:	
Moisture	8.2%
Viscosity @ 600 RPM	25
Filtrate, 30 minutes @ 100 psi	18
Montmorillonite	92%