



## e.drain 6000



### Product Description

**Basic Use:** e.drain 6000 is applied in negative side applications to blindside shoring walls, in positive side applications to over excavated walls, and over plaza decks. e.drain 6000 prefabricated drainage composite is designed to protect the E.Series system assembly, while effectively eliminating the buildup and ponding of water against the membrane assembly.

**Composition:** e.drain 6000 features a lightweight three-dimensional, high-compressive strength polypropylene core and bonded non-woven geotextile fabric. The bonded filter fabric allows water to pass freely into the molded drain while preventing soil particles from entering and clogging the core structure.

### Benefits

- Provides extremely high compressive strength to meet a wide variety of project conditions
- Polypropylene provides greater chemical resistance than traditional polystyrene
- Maintains flexibility in freezing temperatures

### Limitations

- Long-term UV exposure is not recommended

### Technical Data

Properties: See physical properties table

Coverages: 6' x 50' roll covers 300 square feet; 8' x 50' roll covers 400 square feet, not including overlaps or waste

Specification Writer: Contact EPRO before writing specifications on this product. E.Series system assemblies should be reviewed in order to meet project specific site conditions.

### Installation

**Preparation:** Please refer to manufacturer's specifications for substrate requirements. Rolls should be inspected for cosmetic damage prior to application. Substrate must be inspected prior to application to make certain it is in accordance with manufacturer's requirements.

**Application:** Please refer to manufacturer's specifications. Drainage panels may run horizontally or vertically. In blindside shoring applications, secure e.drain to shoring using 2-inch flat washer fasteners every 24 inches on center on seams and terminations and a minimum of every 48 inches on center in the field.

### Availability and Packaging

Contact EPRO sales representative for local distributors or authorized applicators ([www.eproinc.com](http://www.eproinc.com)).

Roll: 6' x 50', 8' X 50'

Weight: 6' rolls = 64 lbs, 8' rolls = 81 lbs

### Warranty

Limited Warranty: EPRO Services, Inc. believes to the best of its knowledge that performance tables are accurate and reliable. EPRO warrants this product to be free from defects. EPRO makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of MERCHANTABILITY OR FITNESS FOR PARTICULAR PURPOSE. EPRO's liability shall be limited in all events to supplying sufficient product to retreat the specific areas to which defective product has been applied. EPRO shall have no other liability, including liability for incidental or resultant damages, whether due to breach of warranty or negligence. This warranty may not be modified or extended by representatives of EPRO or its distributors.

### Equipment

Secure with shot pins using power-actuated fastener or by hand.

### Technical Services and Information

Complete technical services and information are available by contacting EPRO at 800.882.1896 or [www.eproinc.com](http://www.eproinc.com).

This product was formally known as Ecodrain-S6000.



e.drain 6000

## Typical Physical Properties

Physical Property	Test Method	Value
<b>Dimpled Core</b>		
Core Material .....		Polypropylene
Color .....		Black
Dimple Height.....	ASTM D1777 .....	0.4" (10.16 mm)
Compressive Strength .....	ASTM D1621 .....	16,500 psf (790 kN/m <sup>2</sup> )
Flow rate.....	ASTM D4716.....	21 gal/min/ft
<b>Filter Fabric</b>		
Grab Tensile.....	ASTM D4632 .....	100 lbs
CBR Puncture Resistance.....	ASTM D6241 .....	250 lbs
Apparent Operating Size .....	ASTM D4751 .....	70 US Sieve (.0212mm)
Water Flow Rate .....	ASTM D4491 .....	140 gpm/ft <sup>2</sup> (5704 l/min/m <sup>2</sup> )
UV Resistance .....	ASTM D4355.....	70% (500 hrs)

Dimensions: 6' x 50', 8' X 50'

Weight: 6' rolls = 64 lbs, 8' rolls = 81 lbs